

ATF DCT

Mono Grade High Performance Diesel Engine Oil

Description

Petrol Ofisi ATF DCT is an automatic transmission fluid developed to meet the needs of wet DCT type transmission, produced with synthetic base oils and high technological additive package.

Applications

It is used in the following applications:

| | | | |
|---------------|---|--------------|--------------------------------|
| Audi | VW TL 052 182 | Mitsubishi | MZ320065 Dia-Queen SSTF-I |
| Audi | VW TL 052 529 | Nissan | Ford M2C936A |
| BMW (Getrag) | 83 22 2 148 578, 83 22 2 148 579, 83 22 0 440 214, 83 22 2 147 477 | Peugeot | Peugeot/Citroën 9734.S2 |
| Citroën | Peugeot/Citroën 9734.S2 | Porsche (ZF) | Porsche Oil No. 999.917.080.00 |
| Ford/Getrag | Ford M2C936A | Seat | VW TL 052 182 |
| Mercedes-Benz | MB 236.21(001 989 85 03) | Skoda | VW TL 052 182 |
| | | Volkswagen | VW TL 052 182 |
| | | Volvo | 1161838 1161839 |

Benefits

- Maximum wear prevention property
- Extended equipment life
- Longer fluid life
- Gasket and oil seal compatibility

Typical Specifications*

| | | |
|---------------------------------------|-------------|-------|
| Density, @ 15 °C, kg/m ³ | ASTM D 4052 | 0,855 |
| Flash Point, COC, °C | ASTM D 92 | 222 |
| Viscosity, 40 °C, mm ² /s | ASTM D 445 | 42 |
| Viscosity, 100 °C, mm ² /s | | 7,95 |
| Viscosity Index | ASTM D 2270 | 165 |
| Pour Point, °C | ASTM D 97 | -42 |

* Values shown may differ between productions.



Petrol Ofisi