

MAXIMA PRO 5W-30

Fully Synthetic Motor Oil

Description

It is a new generation engine oil formulated with synthetic base oils and special additives, and produced for vehicle engines with emission reducing systems containing DPF and SCR.

Applications

Maxima PRO 5W-30 can be used in diesel passenger cars and light commercial vehicles equipped with exhaust emission systems containing DPF and SCR and requiring engine oil at the ACEA C2 or ACEA C3 performance level, and in gasoline vehicle engines with catalytic converters. It is recommended not to use any additives along with this oil.

Benefits

- Prevents engine wear from the start by reducing friction during start-up.
- Ensures high performance.
- Provides excellent protection even at fast-paced, challenging and high temperature operating conditions.
- Provides fuel efficiency, keeps the engine clean.
- Offers higher resistance against decrement and longer oil change intervals thanks to its improved synthetic formulation.

Performance

ACEA C2/C3, API SN, FIAT 9.55535-S1

Typical Specifications*

SAE Viscosity Grade		5W-30
Density, @ 15 °C, kg/m ³	ASTM D-4052	0,850
Flash Point, COC, °C	ASTM D-92	242
Viscosity, 40 °C, mm ² /s	ASTM D 445	67,1
Viscosity, 100 °C, mm ² /s		11,3
Viscosity Index	ASTM D-2270	166
Pour Point, °C	ASTM D- 97	-33

* Values shown may differ between productions.

